

# LD900 Receiver

Quad-Band GNSS receiver delivers precise positioning for demanding marine operations.

## Maximum Performance

The LD900 is a quad-band GNSS receiver capable of tracking GPS, GLONASS, BeiDou, Galileo and QZSS constellations to provide reliable and accurate positioning. Access to multiple GNSS signals allow for better satellite availability and reduce the impact of satellite masking or blockage.

## Robust L-Band Reception

LD900 receives L-Band signals on multiple channels providing access to the world-wide independent correction links and services provided by VERIPOS. With correction data available simultaneously from up to three correction satellites, the impact of satellite masking can be minimized to ensure reliable reception of correction data.

## Maximum Accuracy

VERIPOS provides accurate and reliable positioning for all marine applications via their redundant positioning and multi-frequency Precise Point Positioning (PPP) Apex and Ultra services. The Apex5 correction service utilizes all GNSS constellations delivering 5cm positioning accuracy for use in the most demanding offshore applications.

## GNSS+INS Integration

SPAN GNSS+INS technology combines GNSS positioning with inertial navigation system (INS) measurements like velocity, attitude and heave. In a solution optimized for hydrographic survey applications, the 3D positioning provides accurate measurements even through extended GNSS outages.

## Simple to Configure and Operate

The intuitive color display and navigation menu makes setup, configuration and system status monitoring simple. The display helps troubleshoot, allowing faults to be quickly diagnosed and resolved. The LD900 can be configured remotely through the VERIPOS Quantum software.

## Designed for Marine Operations

The receiver has been designed, manufactured and delivered specifically for marine operations. Marine certification allows the LD900 to be interfaced into Dynamic Positioning systems, assuring accurate and reliable positioning for critical marine operations.



LD900 Receiver

## Benefits

- Supports decimeter-level multi-constellation positioning with VERIPOS Apex and Ultra PPP correction services
- Compatible with VERIPOS Quantum visualization software
- EN60945 Marine Certified
- OGP 373-19 and IMCA SO15 QC compliant
- Designed for marine operations such as seismic exploration, offshore construction, survey and dynamic positioning
- Advanced signal filtering mitigates the effects of interference from other transmitters

## Features

- 555 channel, all-constellation, multi-frequency positioning solution
- Simultaneously track up to 3 VERIPOS correction service satellites
- Independent L-Band RF input
- Easy-to-use, intuitive, color display for simple configuration and monitoring
- Multiple communication options for interfacing to marine systems
- Built in WiFi support
- Optional SPAN GNSS+INS functionality
- Optional ALIGN GNSS heading solution
- Optional MSK Beacon receives corrections from IALA marine radio beacon network
- Automatic 72 hour rolling data log for incident support

## Primary GNSS Module<sup>1</sup>

### Channel Configuration

555 Channels

### Signal Tracking

GPS	L1 C/A, L1C, L2C, L2P, L5
GLONASS <sup>2</sup>	L1 C/A, L2 C/A, L2P, L3, L5
BeiDou	B1I, B1C, B2I, B2a, B3I
Galileo <sup>3</sup>	E1, E5 AltBOC, E5a, E5b, E6
NavIC (IRNSS)	L5
SBAS	L1, L5
QZSS	L1 C/A, L1C, L2C, L5, L6

### Horizontal Position Accuracy (RMS)

Single Point L1	1.5 m
Single Point L1/L2	1.2 m
SBAS <sup>4</sup>	1 m
VERIPOS DGNSS <sup>5</sup>	1 m
VERIPOS PPP <sup>5</sup>	5 cm
RTK	1 cm + 1 ppm
Initialization time	< 10 s
Initialization reliability	> 99.9%

### Maximum Data Rate

Measurements	up to 20 Hz
Position	up to 20 Hz

### Time to First Fix

Cold start <sup>6</sup>	< 39 s (typical)
Hot start <sup>7</sup>	< 20 s (typical)

### Signal Reacquisition

L1	< 0.5 s (typical)
L2	< 1.0 s (typical)

**Time Accuracy<sup>8</sup>** 20 ns RMS**Velocity Accuracy** < 0.03 m/s RMS**Velocity Limit<sup>9</sup>** 515 m/s

## Secondary GNSS Module<sup>1</sup>

### Channel Configuration

555 Channels

### Signal Tracking<sup>10</sup>

GPS	L1 C/A, L1C, L2C, L2P, L5
GLONASS <sup>2</sup>	L1 C/A, L2C, L2P, L3, L5
BeiDou	B1I, B1C, B2I, B2a
Galileo <sup>11</sup>	E1, E5 AltBOC, E5a, E5b
NavIC (IRNSS)	L5
SBAS	L1, L5

### Time to First Fix

Cold start <sup>6</sup>	< 39 s (typical)
Hot start <sup>7</sup>	< 20 s (typical)

### Signal Reacquisition

L1	< 0.5 s (typical)
L2	< 1.0 s (typical)

**Time Accuracy<sup>8</sup>** 20 ns RMS**Velocity Accuracy** < 0.03 m/s RMS**Velocity Limit<sup>9</sup>** 515 m/s

## L-Band Module

<b>Channels</b>	5 Channels
<b>Frequency Range</b>	1525 to 1560 MHz

## Beacon Module (Option)

<b>Channels</b>	2 Channels
<b>Frequency Range</b>	283.5 to 325.0 kHz
<b>Channel spacing</b>	500 Hz
<b>Demodulation</b>	Minimum Shift Keying (MSK)

## Communication Ports

3 RS-232/RS-422	up to 460,800bps
3 RS-232/RS-422 (expansion)	up to 460,800bps
1 USB 2.0 (host)	HS
2 Ethernet	10/100 Mbps
1 Pulse Per Second output	

## Physical and Electrical

<b>Dimensions</b>	300 x 220 x 80 mm
with mounting plate	300 x 220 x 80 mm

<b>Weight</b>	3.8 kg
with mounting plate	4.8 kg

<b>Power<sup>12</sup></b>	
Power consumption	13 W (typical)
Input voltage	+12 to 24 VDC

### Antenna LNA Power Outputs

Output voltage	12 VDC ±5%
Maximum current	300mA

### Connectors

GNSS RF	TNC
L-band RF	TNC
IALA	TNC
Serial	DB9
Serial (expansion)	DB15
USB (host)	Type A
Ethernet	RJ45
PPS	BNC
Power	M12, 4 pin

### Display

3.5" QVGA TFT Color Display

## ALIGN® GNSS Heading Accuracy

<b>Baseline</b>	<b>Accuracy (RMS)</b>
2 m	0.08 degrees
4 m	0.05 degrees

## SPAN Technology

GNSS+INS integration with marine profile for hydrographic survey applications.

### Supported IMUs:

IMU-ISA-100C  
IMU-ulMU-IC

### Attitude & Velocity Performance

Refer to IMU product sheets for values

### Heave Performance<sup>13</sup>

Instantaneous Heave	5 cm or 5%
Delayed Heave	3.5 cm or 3.5%
Post-Processed Heave	2.5 cm or 2.5% <sup>14</sup>

## Environmental

### Temperature

Operating -15°C to +55°C

### Humidity

EN60945

## Compliance

FCC, CE, RoHS, WEEE, EN60945 (Protected Equipment), EN/IEC62368

## Features

- NovAtel® OEM7® marine positioning engine
- Standard 32 GB internal storage
- Automatic 72 hour rolling data log for incident support
- Simultaneously track up to 3 VERIPOS correction service satellites
- Independent L-Band RF input
- SPAN GNSS+INS option
- ALIGN® GNSS Heading (option)
- Built in WiFi support
- Web GUI
- OGP 373-19 and IMCA S015 (July 2011) QC compliant

<sup>1</sup> Typical values. Performance specifications subject to GNSS system characteristics, Signal-in-Space (SIS) operational degradation, ionospheric and tropospheric conditions, satellite geometry, baseline length, multipath effects and the presence of intentional or unintentional interference sources. <sup>2</sup> Hardware ready for L3 and L5. <sup>3</sup> E1bc and E6bc support only. <sup>4</sup> GPS only. <sup>5</sup> Requires a subscription to a data service. <sup>6</sup> Typical value. No almanac or ephemerides saved and no approximate position or time. <sup>7</sup> Typical value. Almanac or ephemerides and no approximate position and time entered. <sup>8</sup> Time accuracy does not include biases due to RF or antenna delay. No almanac or ephemerides and no approximate position or time. <sup>9</sup> Export licensing restricts operation to a maximum of 515 meters per second, message output impacted above 500 m/s. <sup>10</sup> Model-configurable to track L5/E5a (all / Galileo) through L2 (GPS) or L3/E5b/B2 (GLONASS / Galileo / BeiDou) through L2 (GLONASS). <sup>11</sup> E1bc support only. <sup>12</sup> Typical value. Consult the user documentation for power supply considerations. <sup>13</sup> Requires SPAN Marine Profile. <sup>14</sup> Post-processing results using Waypoint Inertial Explorer.

# Contact Hexagon | VERIPOS

sales@veripos.com +44 1224 965800

For the most recent details of this product visit veripos.com

©2020 VERIPOS. All rights reserved. VERIPOS is part of Hexagon. All trademarks or servicemarks used herein are property of their respective owners. VERIPOS makes no representation or warranty regarding the accuracy of the information in this publication. This document gives only a general description of the product(s) or service(s) offered by VERIPOS, and, except where expressly provided otherwise, shall not form part of any contract. Such information, the products and conditions of supply are subject to change without notice.